

BAS-200 Bio-Acoustic



Advanced
and Reliable.

Dependable Compliance.

The BAS-200 Bio-Acoustic Simulator performs dependable daily calibration checks of the CCA-200 audiometer as required by OSHA 29 CFR 1910.95. Your testing equipment needs to be calibrated daily. Depend on the BAS-200.

Because the BAS-200 is powered by the Benson Medical Instruments audiometer, there is no need to worry about battery life. Connecting the response switch to the BAS-200 returns the system to subject testing.

The BAS-200's advanced design simplifies the daily check and offers greater reliability and repeatability compared to battery-powered units.

Get Started Today

Contact your Benson Medical Instruments dealer for a no-obligation demonstration.

Specifications:

Indicators: power, left response, right response

Test Frequencies: 500 Hz, 1, 2, 3, 4, 6, 8 kHz

Response Threshold: 65 dB HL nominal

Power: supplied by Benson Medical Instruments audiometer

Dimensions: 7 in. x 5 in. x 4 in.

Weight: 1 Lb.

Supplied Accessories:

- Patch cable
- Wall-mounting bracket

- ✓ Quick and accurate daily calibration check as required by OSHA.
- ✓ Uses no batteries: Power is supplied from audiometer.
- ✓ Place on table-top or mount on wall of test booth.
- ✓ No need to remove from system when performing subject testing.
- ✓ Works with standard earphones and Audiocups.
- ✓ Software compatible.



310 Fourth Avenue South
Suite 5000
Minneapolis, MN 55415
U.S.A.

(612) 827-2222